

Elfin I

High Resolution Inkjet Printer



5 inch LCD touch screen
5inch 800*480 color LCD touch screen;



Variable Barcode
Variable barcode printing supported;



Flexibly Set Printing Messages
User can set shifts, counter, date format more flexibly, and also can custom set hex systems.



Communication Protocol & SDK Support
Provide communication protocols and SDK to support system integration projects.



Vector Font Editor
Multi-fonts editing supported;



Smart Detection
Smart detection of external devices;



Timely Database Complement
PC software support database printing, and the data complement can be done timely and efficiently.



OEM/ODM Supports
Offer professional OEM and ODM customized services

Database Complement Function (Optional)

Support database format: MS Excel, MS Access, SQL, MSCSV.



Database



PC Control



Inkjet Printer

Communication Protocols

Support both simplified communication protocols, complete communication protocols and also MODBUS/CC-Link protocol.



Modbus



CC-Link

SDK Support

Support JAVA/C++/C#/Python language, and Android system.



JAVA



C++



C#



Python

&



Android

Technical Parameters

Selectable Languages

Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian;

Barcodes

GS1, UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN 128, PDF417, DATAMATRIX, QR;

Printable Heights (mm)

1~12.7mm

Printing speed

0-60 m/min(300 DPI);

Resolution

50~600DPI

Power Supply

AC 90V-240V/50-60HZ, 60W; (Dedicated AC adaptor)

Printing Objects

Barcodes, Character, Numeric, Logos, Date/Time, Expiry Date, Shift Code, Counter, Lot-Box Code;

Port


- 1) Ethernet: 100Mb/s, Synchronized control of multiple devices via PC;
- 2) USB2.0: Support U-Disk;
- 3) DB15: For external devices like photocell, synchronizer or alarm kit connection;

Mounting

Standard side, downside and anti-shock printing bracket;

Product Certification

CE、FCC;



Dimensions

(H*W*D): 142*65*98mm/ 5.6*2.6*3.9inch(Anti-shock cover is not included)