

EXPERIENCE DURABILITY AND PRECISION WITH THIS HIGH PERFORMANCE WATER-RESISTANT INDUSTRIAL INKJET PRINTER

CLASS: IP65

WATER-RESISTANT & DUSTPROOF







BEVERAGE



COSMETICS



PHARMACEUTICAL



LUMBER



ELECTRONICS



Variable data - support dynamic data, database printing.



Independent controller -10.1 inch colorful LCD capacitive screen.



Maximum printable height 2" – four combined printheads enable the printable height to reach 2".



Independent printhead – printheads are separated from the controller, multi-combinations, easy operation.

TECHNICAL SPECIFICATIONS

TECHNOLOGY WATER-RESISTANT IPG5 VERTICAL PRINT RESOLUTION HORIZONTAL PRINT RESOLUTION MAXIMUM PRINT RESOLUTION MAXIMUM PRINT RESOLUTION MAXIMUM PRINT SPEED MAXIMUM PRINT SPEED THE SPEED OF QR CODE PRINTING UP TO 79PCS/SEC PRINT DISTANCE UP TO 8MM (NOZZLE TO PRINT SURFACE) STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE LOW INK INDICATOR MAXIMUM PRINT SECON SOPPORT AGENCY CERTIFICATIONS LECTRICAL REQUIREMENTS AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGGS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGGS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE PRINTING DIRECTIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGGS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/84 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES INK USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INK USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INK USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INK USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE INC USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE	TECHNICAL SPECIFICATIONS	
VERTICAL PRINT RESOLUTION MAXIMUM PRINT SPEED AUDITION AUDITION MOUNTING PERFORMANCE THE SPEED OF QR CODE PRINTING UP TO 79PCS/SEC UP TO 8MM (NOZZLE TO PRINT SURFACE) STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (258.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W(SPECIFICD AC ADAPTER) AGENCY CERTIFICATIONS IP65 RATED, CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS,	TECHNOLOGY	HP THERMAL INKJET 2.5 TECHNOLOGY
HORIZONTAL PRINT RESOLUTION MAXIMUM PRINT SPEED 200M/MIN (300 DPI) 100M/MIN (600 DPI) PRINTING PERFORMANCE THE SPEED OF QR CODE PRINTING UP TO 79PCS/SEC PRINT DISTANCE UP TO 8MM (NOZZLE TO PRINT SURFACE) STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256,54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (12 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W (SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE PRINTING DIRECTIONS PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM)) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	WATER-RESISTANT	IP65
MAXIMUM PRINT SPEED 200M/MIN (300 DP) 100M/MIN (600 DP) PRINTING PERFORMANCE THE SPEED OF QR CODE PRINTING UP TO 79PCS/SEC PRINT DISTANCE UP TO 8MM (NOZZLE TO PRINT SURFACE) STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS AGENCY CERTIFICATIONS IP65 RATED, CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	VERTICAL PRINT RESOLUTION	600 DPI
PRINTING PERFORMANCE PRINTI DISTANCE UP TO 8MM (NOZZLE TO PRINTING UP TO 79PCS/SEC PRINTI DISTANCE UP TO 8MM (NOZZLE TO PRINTING UP TO 79PCS/SEC STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTIHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS AGENCY CERTIFICATIONS PRINTI CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE PRINTING DIRECTIONS PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	HORIZONTAL PRINT RESOLUTION	40-1200 DP
PRINT DISTANCE STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W (SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	MAXIMUM PRINT SPEED	200M/MIN (300 DPI) 100M/MIN (600 DPI)
STORAGE CAPACITY STORE UP TO 500 MESSAGES TIME & DATE REAL-TIME INTERNAL CLOCK COMMUNICATION INTERFACE COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W(SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, CHINCH COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	PRINTING PERFORMANCE	THE SPEED OF QR CODE PRINTING UP TO 79PCS/SEC
TIME & DATE COMMUNICATION INTERFACE COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W(SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE PRINTING DIRECTIONS PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	PRINT DISTANCE	UP TO 8MM (NOZZLE TO PRINT SURFACE)
COMMUNICATION INTERFACE TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W(SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS IP65 RATED ,CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	STORAGE CAPACITY	STORE UP TO 500 MESSAGES
TOUCHSCREEN 10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY PRINTHEAD CABLE 4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W (SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	TIME & DATE	REAL-TIME INTERNAL CLOCK
PRINTHEAD CABLE LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W (SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS IP65 RATED, CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT AXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	COMMUNICATION INTERFACE	ETHERNET, USB 2.0, AND RS232 PORTS
LOW INK INDICATOR ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W(SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS IP65 RATED, CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	TOUCHSCREEN	10.1 INCH (256.54 MM) FULL COLOR LCD TOUCHSCREEN DISPLAY
INSTALLATION MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING ELECTRICAL REQUIREMENTS 100-240 VAC, 50/60 HZ,24V, 96W (SPECIFIED AC ADAPTER) AGENCY CERTIFICATIONS IP65 RATED, CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	PRINTHEAD CABLE	4 FT (1.2 M) LENGTH, OTHER LENGTHS AVAILABLE
ELECTRICAL REQUIREMENTS AGENCY CERTIFICATIONS IP65 RATED, CE, FCC SOFTWARE SPECIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	LOW INK INDICATOR	ALERT ON TOUCHSCREEN DISPLAY, ALARM LIGHT BEACON IS OPTIONAL
AGENCY CERTIFICATIONS PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	INSTALLATION	MOUNTING BRACKETS FOR SIDE PRINTING OR DOWN PRINTING
PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	ELECTRICAL REQUIREMENTS	100-240 VAC, 50/60 HZ,24V, 96W(SPECIFIED AC ADAPTER)
PRINT CAPABILITY ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	AGENCY CERTIFICATIONS	IP65 RATED ,CE, FCC
DATABASE CAPABILITY ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION AVAILABLE LANGUAGES ENGLISH, CHINESE PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT MAXIMUM PRINT HEIGHT 2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	SOFTWARE SPECIFICATIONS	
AVAILABLE LANGUAGES PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT MAXIMUM PRINT HEIGHT 1/2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1/2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	PRINT CAPABILITY	ALPHANUMERIC TEXT, TIME & DATE, LOGOS, ITEM NUMBERING, SHIFT CODES, BARCODES, AND MORE
PRINTING DIRECTIONS R-L, L-R, INVERT, REPEAT MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT 3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT MAXIMUM PRINT HEIGHT 2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	DATABASE CAPABILITY	ETHERNET COMMUNICATION PROTOCOL FOR EXTERNAL COMMUNICATION
MESSAGE LENGTH UP TO 9.8 FT (3 M) MINIMUM PRINT HEIGHT MAXIMUM PRINT HEIGHT 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	AVAILABLE LANGUAGES	ENGLISH, CHINESE
MINIMUM PRINT HEIGHT MAXIMUM PRINT HEIGHT 2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	PRINTING DIRECTIONS	R-L, L-R, INVERT, REPEAT
MAXIMUM PRINT HEIGHT 2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	MESSAGE LENGTH	UP TO 9.8 FT (3 M)
NUMBER OF PRINT LINES 1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES	MINIMUM PRINT HEIGHT	3/64 INCH (1 MM) OR SINGLE CHARACTER FONT HEIGHT
	MAXIMUM PRINT HEIGHT	2 INCH (50.8 MM) OR SINGLE CHARACTER FONT HEIGHT
INK USAGE AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE	NUMBER OF PRINT LINES	1, 2, 3, 4 OR MORE LINES OF HIGH-RESOLUTION CODES
	INK USAGE	AUTOMATICALLY DETECTS INK TYPE AND CALCULATES USAGE PER MESSAGE

OPTIONAL ACCESSORIES



Photoelectric

Sensor

Rotary

Encoder



Alarm

Light



Floor

Stand

INK SOLUTIONS













A wide range of inks available for both porous and nonporous materials such as flexible film, plastic, glass, treated substrates, paper carton, wood, and metal among others.